

## BW cable glands



Size of Aluminum cable glands	20mm 25mm 32mm 40mm 50mm 63mm 75mm 90 mm 2 part 3 part 4 part cable glands SWA armoured cable glands also gland packs and kits Also available in BRASS
Standard	BS 6121 En series
Application	Dry Indoor, for use with all types of SWA Cable
Function	Provide mechanical Cable Retention & Electrical Wire continuity via Armoured Wire.
Material	Brass BS 2874 CZ121 Pb3
Optional Threads	METRIC, NPT, BSP, PG or as specified
Finish	Brass Finish, Nickel Finish, Chrome Finish or as specified
Operating Temp.	-800 C to +3000 C
Accessories	Matching Accessories available like PVC Shrouds, Aluminium Lock Nuts, Earth Tag, Reducers, Adaptors, etc. as per the requirement

Technical Data:

Size	Thread Size 'C'		Minimum Length of Thread 'D'	Cable Range	
	MM	INCH		MAX 'A'	MAX 'B'
BW 20S	20	3/4	10	13.00	15.50
BW 20L	20	3/4	10	14.00	18.50
BW 25L	25	1	10	20.50	26.00
BW 32L	32	1.1/4	10	27.00	33.90
BW 40L	40	1.1/2	15	33.00	41.50
BW 50S	50	2	15	38.50	47.00
BW 50L	50	2	15	44.00	52.00
BW 63S	63	2.1/2	15	51.00	59.20
BW 63L	63	2.1/2	15	56.50	65.50
BW 75S	75	3	15	63.00	74.00
BW 75L	75	3	15	68.50	79.50
BW 90L	90	3.1/2	20		

---

**ADDEESS:**

**CONEX ALUMINIUM COMPONENTS**

Plot 12, GIDC Ind estate  
 Udyognagar  
 Jamnagar 361005 Gujarat

**CONTACTS:**

PHONE : 91-22-43449300  
 FAX : 91-22-22834046  
 EMAIL : [sales@conexaluminium.com](mailto:sales@conexaluminium.com)  
[CONTACT US](#) | [BACK TO HOME PAGE](#)

**KEYWORDS:**