

CW Aluminium Cable glands Armoured Cable glands

CW Aluminium Cable Glands Armoured Cable Glands



Metal Gland Armoured IP66 Features

- A special wedge seal causes the seal to deflect inwards - better than traditional Brass and Aluminium cable glands
- These Aluminum cable glands can be Nickel plated for superior corrosion protection if needed
- Suitable for unarmoured PVC and XLPE insulated armoured cables
- Conform to BS6121: Part 1:1989 and European norms.

CW TYPE CABLE GLANDS ALUMINIUM CABLE GLANDS ARMoured ALUMINIUM CABLE GLANDS CW TYPE

Part No.	Mounting Thread (mm)		Cable Dimensions Accomodated (mm)							Std Qty	
	Diam. C	Length D	Diameter		Armour Wire Diameter	Dim. Across Corners E	Shroud Part No.				
			Under Armour A	Overall B							
									Min		Max
CW20/16 20	15	-	8.6	8	13.4	0.9/1.25	24.5	SH1	20		
CW20S 20	10	-	11.6	11.4	15.9	0.9/1.25	26.5	SH1	20		
CW20 20	10	-	13.9	15	20.9	0.9/1.25	33	SH2	20		
CW25 25	10	-	19.9	20.3	27.4	1.25/1.6	39.9	SH3	10		
CW32 32	15	-	26.2	26	33.9	1.6/2.0	46	SH4	5		
CW40 40	15	-	32.1	31	40.4	1.6/2.0	55.3	SH5	3		
CW50S 50	15	-	38.1	36.5	46.7	2.0/2.5	61.3	SH6	2		
CW50 50	15	-	44	43	53.1	2.0/2.5	66.8	SH7	2		
CW63S 63	15	-	50	48.9	59.4	2.5	77.5	SH7	1		
CW63 63	15	-	55.9	58	65.9	2.5	83.2	SH7	1		

ADDEESS:

CONTACTS:

CONEX ALUMINIUM COMPONENTS

Plot 12, GIDC Ind estate
Udyognagar
Jamnagar 361005 Gujarat

PHONE : 91-22-43449300

FAX : 91-22-22834046

EMAIL : sales@conexaluminium.com

[CONTACT US](#) | [BACK TO HOME PAGE](#)

KEYWORDS: